



Features

- Solid Aluminum Die-casting chassis
- Variety of LCD panel type selections
- Front bezel IP65
- VGA / DVI / input
- 9~36V DC wide range power input

Specifications

LCD

Display Type	21.5" TFT-LCD
Max. Resolution	1920x1080
Max. Color	16.7M
Luminance (cd/m ²)	250
View Angle	H:178 / V:178°
Backlight Lifetime	30,000 hrs
Contrast	3000:1
Power Consumption	Max:24W

System

OSD Control Membrane	On board controller, extendable key pad from connector Transfer Board OSD Membrane Keypad
External I/O Port	1 x VGA, 1 x DVI, 1 x RCA 1 x 3 pins terminal block 1 x USB for Touch Control Optional: 1 x DB-9 for Resistive Touch control 1x Line in by Phone Jack
Power Input	9~36V DC
Touch Screen	121:Resistive Touch Window 121P:Projected Capacitive Touch
Light Transmission	ARCDIS-121:80% ARCDIS-121P:90%

Mechanical

Construction	Aluminum Die-casting chassis
IP Rating	IP65 front panel
Mounting	Panel mounting, VESA 100x 100
Dimension(mm)	557 x 362 x 64.8 mm
Net Weight	7.6Kg

Environmental

Operating Temperature	0~50 °C
Storage Temperature	-20~60 °C
Storage Humidity	10 to 90% @ 40°C, non- condensing
Certificate	CE/FCC Class A

Dimension

