



DATA SOUND - LABORATORIES -


.....
EMBEDDING THE FUTURE



**Electronic
Design**



**Panel
PC / HMI**



**Single Board
Computer**



**Industrial
PC**



Call us on +44(0)1462 675330



Email us at sales@dsl-ltd.co.uk

Why choose DSL?

- Over 25 Years Industry Experience
- 5 Years Warranty on all Products
- Evaluation Products Available
- Lifetime Technical Support

Our Services

- Electronic Design
- Production Management
- Assembly and Test
- Bespoke BIOS Creation
- Industrial Embedded PC Solutions



www.dsl-ltd.co.uk



Features

- 15" TFT LED Backlight LCD
- 4th Generation Intel Core i7/i5/i3 Panel PC
- Intel Q87
- 2 x DDR3 1066/1333/1600MHz SO-DIMM, up to 16GB System Memory
- Fanless Design
- Support 1 x PCIe x16
- Wide range DC 11~32V Power Input
- IP65 Compliant Front Panel

Specifications

System

Processor	Socket LGA 1150, 4th Gen. Intel Core i7/i5/i3 Intel Core i7-4770TE 2.3G 8M(TDP: 45W) Intel Core i5-4570TE 2.7G 4M(TDP: 35W) Intel Core i3-4330TE 2.4G 4M(TDP: 35W)
System Chipset	Intel Q87
System Memory	2 x 204-pin DDR3 SO-DIMM, up to 16GB 1066/1333/1600MHz

External I/O

USB	4 x USB 3.0 Type A 2 x USB 2.0 Type A by cable (option)
Serial/Parallel	3 x RS-232/422/485 DB-9, COM1, COM2, and COM3, Default RS-232
Audio	1 x Mic-in, Line-out
LAN	2 x GbE RJ-45
VGA	1 x VGA
Power	1 x DC Power 3-pin Terminal Block Connector 1 x Rocker Switch for Power on/off
Others	2 x LED Indication for Power and HDD 1 x 8-pin Terminal Block 3 in/3 out/VCC/GND (option) 1 x CF Slot (option)

Expansion

Expansion Slot	1 x PCIe x16 slot 1 x mSATA or 1 x Mini-PCIe slot for WIFI/BT/3G/GPS (option)
----------------	----------------------------------------------------------------------------------

Storage Space

Storage	2 x 2.5" SATA HDD Space, Easy Accessible, RAID 0.1
---------	----------------------------------------------------


LCD

Display Type	15" color TFT LCD
Max. Resolution	1024 x 768
Max. Color	16.7M
Contrast Ratio	800: 1
Luminance (cd/m ²)	400
View Angle	160 (H) / 140 (V)
Backlight Lifetime	50,000 hrs

Touch Screen

Type	Resistive Touch Screen/Projective Capacitive Touch Screen
Interface	USB
Light transmission (%)	Over 80%(Resistive) Over 90%(Projected Capacitive)

Dimensions



Power

Power input	11~32V DC
Power Consumption	MAX: 45.1W

Mechanical

Front Bezel	Steel Black or Aluminum with Resistive Touch Aluminum with Projected Capacitive Touch (only Flat Bezel Designed)
Rear Bezel	Steel Black
Mounting	Panel mount/VESA Mount 75 x 75
IP Rating	IP65 Compliant Front Panel
Dimension	410 x 310 x 122.5 mm
Net Weight	9.5Kg

Environmental

Operating temperature(°C)	0~50°C
Storage temperature(°C)	-30~70°C
Storage humidity	10 to 90% @ 40°C, non- condensing
Certificate	CE / FCC Class A

Operating System Support

Windows 7 Professional for Embedded Systems
Windows 7 Ultimate for Embedded Systems
Windows Embedded 8.1 Pro
Windows Embedded 8.1 Industry Pro

Ordering information

APC-3519AT (Barebone)	15" XGA Intel Core i processor comes with Intel Q87 chipset, fanless design panel PC(w/o CPU/RAM/HDD), 1 x PCIe x16 slot, resistive touch, 11~32VDC power input with adaptor, black steel enclosure.
APC-3519AT-01	15" XGA Intel 4th Core i5-4570TE 2.70G processor comes with Intel Q87 chipset, fanless design panel PC, 4GB DDR3 memory, 320GB SATA 2 HDD, 1 x PCIe x16 slot, resistive touch, 11~32VDC power input with adaptor, black steel enclosure.